

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5800)

Marked a Fir 6" dia., for ¼ sec. cor., from which
A Fir 30" dia., bears N.85°W., 23 lks. dist.
A Chinquapin 6" dia., bears S.20°E., 16 lks. dist.

H.L. Eppstein, County Surveyor - Wit: Harley Johnson; B.A. Lane; G.C. Sellers - March 4, 1930 - C.S. File 14/58 and Vol. 4 Page 69

Set 1¼" x 2 ft. Ford shaft from one old BT, a 30" Fir.
Marked new BTs:
W.Fir 16" dia., bears N.44°30'W., 96 ft.
W.Fir 14" dia., bears N.35°00'E., 120.5 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; J. Fee, crew - Aug. 28, 1957 - C.S. File 49/12-5

Found - Steel axle set by Eppstein in 1930.
W.Fir, now 30" dia., N.35°E., 121.4 ft., showing good scars.
W.Fir stump, now 32" dia., N.44°W., 96.6 ft., chopped out blaze and found BT scribe in good condition.
Old rotted Fir stump bears N.86°W., 15.6 ft.
A clump of small Chinquapins bears S.20°E., 13 ft.
New BT - An 8" D.Fir bears S.88°W., 19.4 ft. scribe "¼ S11 CS BT"

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1278, Surveyed July/Oct. 1985 - (DCSO records Vol. 48 Page(s) 18256-57)

The ¼ sec. cor., perpetuated and recorded by Eppstein in 1930, monumented with a steel rod, 24" long, 1½" dia., loosely set 18" in the ground, from which the remains of an original bearing tree:

A decayed Fir stump 26" dia., bears N.85°W., 23 lks. dist., no marks remaining.
and the remains of BTs mkd. by Eppstein:
A Fir stump 41" dia., bears N.35°E., 183 lks. dist., with healed blaze.
A rotted Fir stump 30" dia., bears N.44½°W., 145 lks. dist., no marks remaining.

At the corner point
(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an stainless steel post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

T 28 S R 8 W
 ^{1/4}
 S 11 | S 12
 1985

from which new bearing objects, no suitable trees available

A Fir stump 29" dia., bears S.72¹/₄°E., 66 lks. dist. mkd. X BT.

A Fir stump 16" dia., bears S.88°W., 30 lks. dist. mkd. X BT.

Reset the steel rod alongside.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post, and set a steel fence post alongside the corner.