

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 1 and 2

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

| |
|--|
| <p>GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5801)</p> <p>-----</p> <p>Set ¼ sec. post, from which A B.Oak 24" dia., bears N.82°E., 44 lks. dist. A B.Oak 12" dia., bears N.58°W., 94 lks. dist.</p> |
| <p>Survey by Marvin C. Ramsey - For: J.H. Baxter & Co. - Filed Jan. 26, 1960 - C.S. File 51/65</p> <p>-----</p> <p>Unable to find any evidence of the original corner. Set an Iron pipe 3 ft. long, 1½" dia., 28" in the ground mkd. RS404, from which 8" W.Oak bears S.19 ¾°E., 145 lks. dist. mkd. ¼ S1 RS404 BT. 8" W.Oak bears S.2 ¾°W., 245 lks. dist. mkd. ¼ S2 RS404 BT.</p> |
| <p>Fd. OK, March 1975 by V.McLind - M 55-57</p> |
| <p>Survey by Ronald G. Geisler - For: Champion International Corp. - Nov. 1985/Jan. 1986 - M 90-79</p> <p>-----</p> <p>Set 2½" alum. cap on a 2½" x 30" alum. flared pipe in a cultivated field. Ramsey's 1960 1½" I.P. bears S.04°23'09"W., 15.88 ft. New BTs- 11" Fir bears S.74°W., 188.0 ft. scribed ¼ S2 BT. 9" Oak bears S.63°E., 143.4 ft. scribed ¼ S1 BT. An unrecorded 1" I.P. bears N.87°47'28"E., 12.76 ft. from corner.</p> |
| <p>Fd. OK, Sept. 1993 by G. Baughman - Land partition 1993-0067 Fd. Ok by Gary Smithers, June 2007 - M153-42</p> |
| <p> </p> |