

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 1, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5793)

-----  
Set ¼ sec. post, from which  
A W.Oak 20" dia., bears N.10°W., 96 lks. dist.  
A B.Oak 12" dia., bears S.61°E., 78 lks. dist.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated May 6, 1924 (DCSO records Vol. 14 Page(s) 6003)

-----  
The point for ¼ sec. cor., located by record measurement from the original bearing trees on which the blazes are plain.  
At the exact cor. point  
Set an iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor., with brass cap mkd: ¼  $\frac{S\ 36}{S\ 1}$   
1924

from which the original bearing trees:  
A B.Oak 20" dia., bears S.69°E., 78 lks. dist. (Not S.61°E.)  
A W.Oak 30" dia., bears N.8°W., 96 lks. dist. (Not N.10°W.)  
New Bearing trees:  
A Fir 12" dia., bears N.18°E., 28 lks. dist. mkd. ¼ S36 BT  
A Fir 10" dia., bears S.16°E., 21 lks. dist. mkd. ¼ S1 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Cliff Stone, crew - Nov/Dec. 1966 - C.S. File 54/38-7

-----  
Found - GLO brass cap, properly mkd. in 1924.  
No trace of 1924 BTs. Evidently removed when fence was put in.  
Orig. 20" B.Oak, now down, S.69°E., 51.5 ft., opened for scribe "S".  
Orig. 30" W.Oak, now down, N.8°W., 63.4 ft.  
New BTs- 6" D.Fir S.42°E., 59.0 ft. mkd. ¼ S1 CS BT.  
18" D.Fir North 45.7 ft. mkd. ¼ S36 CS BT.  
This corner lies North of fence corner 1.5 ft.

FD. brass cap by N. Hibbs, 12/2007 - 2007-0168