

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 640240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1483, surveyed May/July 1989 - (DCSO records Vol. 50 Page(s) 18852)

Point for the center ¼ sec. cor. of sec. 25, at intersection with the E. and W. center line.

Set a stainless steel post 28" long, 2½" dia., 24" in the ground with brass cap mkd. T 28 S R 8 W

C¼
S 25
1989

from which

A Fir 15" dia., bears N.69°E., 24 lks. dist. mkd. C¼ S25 BT.

A Fir 16" dia., bears N.49°W., 32 lks. dist. mkd. X BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Carl Sweeden - For: Emma Wageman Trust - June 2012 - M163-67

Found - 3¼" BLM brass cap "1989", up 0.50'
20" D.Fir BT, N.69°E., 16.5' to Bole (15.84') tag & scar vis.
19" D.fir BT, N.49°W. 21.1' to Bole, tag & scar vis.