

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5797)

Set ¼ sec. post, from which
A W.Oak 18" dia., bears N.52°E., 91 lks. dist.
A W.Oak 10" dia., bears S.48°E., 163 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Oct. 16, 1957 - C.S. File 49/12-14

Found - Brass cap set by Mensch, 1924 survey, marked: U.S. GLO survey 1924 ¼ S24 S25.
10" W.Oak bears S.36°E., 11.6 ft. I open and find scribe marks. This BT probably scribed in 1924 Orig. 18" now 36" W.Oak BT, N.52°E., (Rec. 60.1 ft.), I find to be 56.6 ft. I open and find original scribe mark "S".
No record can be found of Mensch's survey of sec. 25, T28S R8W. See letter dated Oct. 1, 1957 from BLM, Leonard Berlin.
New BTs- 12" W.Oak bears S.7°E., 9.5 ft. scribed ¼ S25 CS BT.
14" W.Oak bears N.67°W., 40.7 ft. scribed ¼ S25 CSBT

Cor. Fd. and used in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1483, surveyed May/July 1989 - (DCSO records Vol. 50 Page(s) 18852-53)

Found OK by C. Sweeden, Sept. 2003 - M143-8