

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5792)

Set post, for cor. of T's. 28 & 29 S., R's. 7 & 8 W., from which

- A W. Oak, 10" diam., bears N.0°30'E., 256 lks.
- A W. Oak, 20" diam., bears S.76 3/4°E., 157 lks.
- A W. Oak, 20" diam., bears S.27°W., 702 lks.
- A B. Oak, 12" diam., bears N.5°W., 333 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 5924)

Intersect the point for cor. of Tps. 28 & 29S., R's 7 & 8W., established by Hathorn, located by bearing and measurement from the original NE. & NW. bearing trees, on which the marks are legible. The original SE. and SW. bearing trees are not found.

At the exact point

Set an iron post, 3 ft. long, 3" diam., b 27" in the ground, for cor. of Tps. 28 & 29S., R8W., with brass cap marked

T28S
R8W _____ S36
 S 1
 T29S
 1924

from which (new bearing trees)

- A W. Oak, 12" diam., bears S.5½°W., 168 lks., marked T29S R8W S1 BT.
- A W. Oak, 7" diam., bears N.21 3/4°W., 166 lks., marked T28S R8W S36 BT.

Original NE. bearing tree, a W. Oak, 20" diam., bears N.0°30'E., 256 lks.

Original NW. bearing tree, a B. Oak, 24" diam., bears N.5°W., 335 lks.

James W. Byron, Dep. Co. Surveyor - Milo Godfrey & Clete Putnam - April 1961 - C.S. 49/50-46

Corner to sec. 36, T28-8 & sec. 1 T29-8.

Found- Brass cap in E. W. fence line. Bt's. still alive.

N.E. BT., center rotted, shows good reverse scribing "W 28".

New BT:

6" W. Oak, bears N.9°E., 26.4 ft., scribed T28S R8W CS BT.

(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveys Office - R.W. Smith, S.J. Flause -
June 16, 1987 - C.S. 62/45-19

(corner report only)

Found -

A 1924 GLO 3¼" brass cap properly mkd. on a 3" diam. I.P.
protruding 1 ft. above ground.

10" now 22" diam., W. Oak with a fully healed blaze,
reverse scribing is seen through hole in backside of
tree "T28S R7W S31" bears N.0½°E., 169 ft. Orig. BT,
agrees with rec.

12" B. Oak, now stump hole bears N.5°W., 219.8 ft.
(N.5°W., 221.10 ft. per 1924 GLO agrees well with rec.)
Orig. BT (Another tree has in the past been mistaken as
the BT. we opened it and found no scribing. This is a
21" W. Oak which bears N.7½°W., 241.7 ft. with a 1961
BT tag having orig. NW BT bearings and distances marked
on tag.)

7" now 11' diam., W. Oak, with a single fully healed blaze
bears N.21 3/4°W., 109.6 ft., agrees with record. 1924
BT.

No other orig. or 1924 BTs found.

6" now 13" diam., W. Oak with a fully healed double blaze
bears N.9°E., 26.4 ft. agrees with record. (Byron)

Corner lies in a west running fence line approx. 100 ft. west
from the intersection of a north-south fence and west running
fence.