

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T28-7½

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5790)

Set post cor. secs. 18, 19, 13 and 24, from which
A Laurel 18" dia., bears S.89 3/4°W., 35 lks. dist.
A Laurel 10" dia., bears N.45°W., 65 lks. dist.
A B.Oak 12" dia., bears S.35°E., 33 lks. dist.
A B.Oak 6" dia., bears N.32°E., 45 lks. dist.

GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pg. 5916)

Intersect the point for cor. of secs. 13, 18, 19 and 24, located by record measurement from the orig. SW and NW BTs upon which the old blazes are plain. The NE tree is gone and the SE tree has rotted down, but the marks are still legible. At the exact cor. point
Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd:

T28S
R8W:R7½W
S13:S18
S24:S19
1924

from which new bearing trees

A Fir 20" dia., bears N.3°E., 57 lks. mkd. T28S R7½W S18 BT.

A Laurel 36" dia., bears S.43°E., 43 lks. dist., mkd. T28S R7½W S19 BT.

Original BTs

A Laurel 36" dia., bears S.89 3/4°W., 35 lks., re-marked T28S R8W S24 BT.

A Laurel 30" dia., bears N.45°W., 65 lks. dist., remarked T28S R8W S13 BT.

FD. Ok by D. Edwards, 8/2009 - M159-62