

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5790)

Set 1/4 sec. post, from which
A Fir 12" dia., bears N.63°E., 9 lks. dist.
A Fir 6" dia., bears N.34°W., 40 lks. dist.
(Old 1/4 post bears North 16.60 chains and East 3.37 chs. - Ford Survey)

GLO resurvey by Mensch, 1924 - (DCSO records, Vol. 14 Pages 5915-16)

Intersect the point for 1/4 sec. cor., located by measurement from the original bearing trees. The blazes are plain but marks are grown over.

At the exact corner point
Set an iron post, 3 ft. long, 1 ins. diam., 28 ins. in the ground, with brass cap mkd:

1/4
S13 | S18
 | R7 1/2
 |
 1924

from which (original bearing trees)
A Fir 24" dia., bears N.63°E., 9 lks. dist. re-marked 1/4 S18 R7 1/2 BT.
A Fir 10" dia., bears N.31°W. (not N.34°W.) 40 lks. re-marked 1/4 S 13 BT.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-7

Found - Brass cap at corner. NE BT now snag. NW BT OK.
New BT - 12" W.Fir bears S.5°E., 13.5 ft. scribed 1/4 S18 CSBT

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/14/1998 - C.S. File 66/2-32

Found - 2 1/2" dia., brass cap on a 1" OD iron pipe, protrudes 5" above ground, properly marked. Note: brass cap orientated Southeast.

Orig. NE BT now gone.

6" Fir, now rotted to ground stump, scribing found "4S13BT" bears N.31°W., 26.4'. (Agrees with ren records) OBT

1961 DCSO BT now rotted Fir remains near record "S.5°E., 13.5 ft." No scribing found.

New BTs- 6" dia., D.Fir, double blazed and scribed "1/4 S18 CS BT" bears S.61°E., 4.8'.

(Cont. next page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13; S18 T28-7 1/2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

10" dia., G.Fir, double blazed and scribed "1/4 S13
CS BT" bears N.41 1/2°W., 21.0'.
8" dia., G.Fir, double blazed and scribed "1/4 S13 CS
BT" bears S.87°W., 28.5'.
Corner lies approx. S.45°W., 100' from end of road.

FD. Ok by D. Edwards, 8/2009 - M159-62