

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. cor. 1 & 12; 6 & 7, T28-7½

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 14 Page 5789)

-----  
Set post for cor. secs. 6,7, 1 and 12, from which  
A Fir 12" dia., bears S.18°W., 19 lks. dist.  
A Fir 15" dia., bears N.70°W., 52 lks. dist.  
An Oak 9" dia., bears N.1°E., 25 lks. dist.  
A Laurel 8" dia., bears S.52°E., 53 lks. dist.  
(Corner previously set bears North 11.08 chs. and East 4.55 chains. (Ford's corner)

GL0 resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5912-13)

-----  
Intersect the point for cor. of secs. 1, 6, 7 and 12, located by record measurements from the SE., SW., and NW. bearing trees. The NE tree has rotted away and the SE tree is now dead. At the exact corner point  
Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd:

T28S	
R8W	R7½W
S1	S6
S12	S7
1924	

from which  
A W.Fir 12" dia., bears N.35½°E., 36 lks. dist. mkd. T28S R7½W S6 BT. (New BT)  
A Chinquapin 9" dia., bears S.32°E., 46 lks. dist. mkd. T28S R7½W S7 BT (New BT)  
A Fir 14" dia., bears S.19°W., (Not S.18°W.) 19 lks. (old bearing tree, marks legible)  
A Fir 36" dia., bears N.70°W., 52 lks. dist., (old bearing tree, marks legible.)

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey - July 29, 1957 - C.S. File 49/5-8

-----  
Found - 2" I.P. with brass cap mkd. "U.S. General Land Office Survey"  
32" Fir N.72°W., 34.8 ft. showing good scar, did not chop out.  
18" W.Fir N.37°E., 23.8 ft. showing good scar, did not chop out.  
14" Fir S.19°W., uprooted and down.  
Chinquapin brush growing at location for SE BT.  
(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T28-7½

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -22" D.Fir S.70½°W., 22.6 ft. Bark scribe "T28S R8W S12 CS BT".  
8" I.Cedar S.49°E., 28.5 ft. Blaze & scribe "T28S R7½W S7 CS BT".

Ronald Geisler, L.S. #1988 For: Champion International - Nov. 1985-Jan. 1986 - M 90-79

-----  
Found - 1924 GLO 2½" brass cap on a 2" I.P.  
14" Fir, uprooted and down, bears S.19°W., 12.5 ft. No scribing. (Orig.)  
18" Fir, now badly splintered stump and downed tree, bears N.37°E., 23.8 ft., scribed "T28S R7½W. (1924)  
13" I.Cedar bears S.49°E., 28.5 ft. Closed face. (1957)  
New BTs -10" Cedar bears N.42°W., 16.4 ft. scribed "T28S R8W S1 BT"  
4" Fir bears N.17°E., 10.3 ft. scribed "X BT".  
8" Fir bears S.26°W., 27.4 ft. scribed "T28S R8W S12 BT".