

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 1; & 6, T28-7 1/2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Mensch, 1924 (DCSO records, Vol. 14 Page 5912)

-----  
Apportioned distance,  
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground, with brass cap mkd: 1/4

S1 | S6  
    | R7 1/2  
    1924

from which

A Chinquapin 8" dia., bears N.87°E., 26 lks. dist. mkd.  
1/4 S6 R7 1/2 BT.

A Fir 12" dia., bears N.78°W., 75 lks. dist., mkd.  
1/4 S1 BT.

Note: At 1/4 sec. cors. referring to T28S R7 1/2 W., the marks R7 1/2  
are placed upon corners and bearing trees to distinguish  
these cors. referring to old secs. of the same designation of  
T28S R7W.

Doug. County Surveyors Office - James Byron, Deputy - Milo  
Godfrey; Clete Putnam - May 1961 - C.S. File 52/79-12

-----  
Found - Brass cap and NW BT, now stump. SE BT is OK.  
New BT - 17" R.Fir bears N.70°W., 37.0 ft. recently scribed  
1/4 S1 and other scribing.

Fd. OK, Nov. 1985 by R. Geisler - M 90-79