

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Dennis Hathorn, under Contract #57 dated April 12, 1855 (DCSO records, Vol. 12 Page 5231)

-----  
Set post, Standard cor. of Tp. 28 S., Rs. 7 and 8 W., from which

A B.Oak 10" dia., bears S.8°W., 44 lks. dist.

A B.Oak 12" dia., bears S.61°E., 184 lks. dist.

-----  
GLO resurvey by Mensch, 1924 (DCSO records, Vol. 14 Pages 5853-54)

-----  
Intersect the cor. established by Hathorn for standard cor. of T.28S. Rs. 7 and 8 W., located by measurement from the original bearing trees. Old blaze on SE tree has been opened and marks are plain. SW tree is a decayed stump, old blazes visible.

At the exact cor. point

Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for cor. of T. 28 S., Rs. 7½ and 8 W., with brass cap mkd:

S 1	S 6
R8W	R7½W
T28S	
1924	

from which (new bearing trees)

A Fir 20" dia., bears S.29°E., 52 lks. dist. mkd. T28S R7½W S6 BT.

A Fir 20" dia., bears S.12°W., 47 lks. dist. mkd. T28S R8W S1 BT.

Orig. BTs

A B.Oak 16" dia., bears S.62°E., (instead of S.61°E.) 184 lks. dist.

Stump of B.Oak 10" dia., bears S.3°W., (instead of S.8°W.) 44 lks. dist.

-----  
H.L. Eppstein, Wit: B.A. Lane; Lige Mathews - June 1930 - M 1-73; C.S. File 14/59

-----  
This corner was set by me in 1922. Reset by Mensch in 1924 with standard gov't post. I marked witness tees which were not changed:

R.Fir 24" dia., bears S.30°30'E., 32.8 ft. mkd. C.S. T28S R7W S6 BT.

R.Fir 30" dia., bears S.11°W., 29.5 ft. mkd. C.S. T28S R8W S1 BT.

(Cont. Next Page)

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald Geisler, L.S. #1988 - For: Champion International -  
Nov. 1985-Jan. 1986 - M 90-79

-----

Found - 1924 GLO 3¼" brass cap on a 3" I.P.  
23" rotted fir stump, 3 ft. tall, bears S.12°W.,  
30.3 ft. (Rec. 31.0 ft.) No scribing. 1924  
25" rotted Fir stump bears S.29°E., 34.3 ft. No  
scribing. (1924)  
New BTs -8" Fir bears S.6½°E., 136.0 ft. scribed T28S R7½W S6  
BT.  
8" Fir bears S.31°W., 198.3 ft. scribed T28S R8W S1  
BT.