

TOWNSHIP 28 RANGE 08 POINT IDENTIFIER # 915110

PRIMARY CORNER DESCRIPTION Cor. #3, Tract #62

Alias 916100 Description Cor. #2, Tract #63

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

GL0 resurvey by Fred Mensch , U.S. Cadastral Engineer - under special Instructions, dated April 18, 1924 - (DCSO records Vol. 14 Page(s) 5906)

Point for S. 1/16 sec. cor., on W. bdy. of original sec. 31. Set an iron post 3 ft. long, 1" dia., 28" in the ground, for cor. No. 3 of this survey, identical with Cor. No. 2 of Tract No. 63, with brass cap marked:

TR 62
AP 3
AP 2
TR 63
1924

from which

A Fir 10" dia., bears N.18°E., 28 lks. dist., mkd. A P 3 TR 62 BT.

A Fir 6" dia., bears S.36°E., 32 lks. dist., mkd. A P 2 TR 63 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - April 1961 - C.S. File 49/50-47

Found brass cap and NE. BT, in good condition. Stump of SE. BT.

New BT - 18" R.Fir bears S.6°E., 17.0 ft. scribed AP 2 TR 63 CS BT.