

PRIMARY CORNER DESCRIPTION AP 3 Tract 63 & AP 2 Tract 47

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Nathaniel Ford, Deputy Surveyor, under Contract #44, dated May 30, 1854 - (DCSO records Vol. 14 Page(s) 5746)

Set a post cor. of secs. 1, 6, 31, & 36, from which

- A B.Oak, 15" dia., bears N.46°W., 142 lks.
- A B.Oak, 12" dia., bears S.45°W., 52 lks.
- A W.Oak, 12" dia., bears N.63°E., 225 lks.
- A B.Oak, 20" dia., bears S.21°E., 110 lks.

Douglas Co. Surveyors Office - G.G. Stewart - For: I.B. Nichols et al - Nov. 8, 1922 - M 3-74 & C.S. 5/28 & Vol. 3 Pg. 129

-
- Found - OBTs
 - Set - Iron pipe
 - BT remarked.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated April 18, 1924 - (DCSO records Vol. 14 Page(s) 5908-9)

Intersect the old corner of Tps. 28 & 29 S., R7 & 8 W., established by Ford, which is an iron pipe, 1" dia., 4" above ground, restored by County Surveyor; from which the OBTs:

- A W.Oak, 16" dia., bears N.63°E., 225 lks., old marks legible.
- A W.Oak, 30" dia., bears S.22°E., 107 lks., old marks legible.
- A W.Oak, 30" dia., bears S.33°W., 50 lks., old marks legible.
- A B.Oak, 36" dia., bears N.42½°W., 140 lks., old marks legible.

Alongside the iron pipe

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for cor. #3 of this survey, identical with cor. #2 of TR #47, T29-7 with brass cap mkd:

TR63|
AP 4|
AP 1|
TR47|
1924

from which

- A Fir, 26" dia., bears N.30°E., 45 lks., mkd: AP 3 TR 63 BT.
- A Fir, 14" dia., bears S.39°E., 41 lks., mkd: AP 2 TR 47 BT.

