

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor S. 31; NW Cor S. 6, T30-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Contract #797, dated April 19, 1910 - (DCSO records Vol. 15 Page(s) 6132)

-----  
At a point on the Willamette Meridian, 43.20 chs. South of the SE. cor. of T29S R1W, I establish cor. for Tps. 29 and 30 S., R 1 E, as follows:

Set a conglomerate stone 15x12x10 ins., 10" in the ground for cor. marked with 6 notches on N., E., and S. edges, from which

A Cedar 10" dia., bears N.61°E., 12 lks. dist. mkd. T29S R1E S31 BT.

A Fir 24" dia., bears S.49°E., 19 lks. dist. mkd. T30S R1E S6 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Feb. 1968 - C.S. File 54/59-79

-----  
Found - 24" D.Fir, now down, S.49°E., 12.5 ft.  
10" Cedar now 13", N.61°E., 7.9 ft., opened for scribe "BT".

Stone at township corner. No marks.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S  
R 1 S1 | S 31 R  
          | S 6 1  
W 1968 E

New BTs- 15" Fir N.27°E., 12.3 ft. mkd. T29S R1E S31 CS BT.  
31" D.Fir S.58°E., 29.0 ft. mkd. T30S R1E S6 CS BT.  
12" D.Fir S.76°W., 16.4 ft. mkd. T30S R1W S1 CS BT.