

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Contract #797 dated April 19, 1910 - (DCSO records Vol. 15 Page(s) 6133)

Set a basalt stone 15x10x8 ins., 10" in the ground for ¼ sec. cor. on W. bdy. sec. 31, marked ¼ on E. face, from which
A Fir 5" dia., bears N.19°E., 4 lks. dist. mkd. ¼ S31 BT
A Madrone 6" dia., bears S.42°E., 48 lks. dist. mkd. ¼ S31 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 12, 1968 - C.S. File 54/59-84

Found - 5" Fir, down and out of place, opened for scribe "¼"
6" Laurel, now dead and out of place, S.42°E., 31.7 ft., found possible scribe marks.
40" Pine stump, probably line tree, 139.3 ft. North of corner.

By using line tree and Laurel BT, I set a brass cap at cor. mkd:

County Surveyors Office
T 29 S R 1 E
¼ | S 31
1968

New BTs- 12" Fir S.75°E., 23.0 ft. mkd. ¼ S31 CS BT.
12" Y.Pine N.71°E., 36.3 ft. mkd. ¼ S31 CS BT.
Corner lies 211.2 ft. South of Tsp. Corner.