

PRIMARY CORNER DESCRIPTION SE. Cor. Section 36, T29-1W

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 14 Page(s) 6059)

Set post, from which

- A Fir 15" dia., bears N.31°W., 21 lks. dist.
- A Fir 10" dia., bears N.45°E., 33 lks. dist.
- A Laurel 12" dia., bears S.70°W., 38 lks. dist.
- A Laurel 12" dia., bears S.10°E., 26 lks. dist.

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6686-87)

At a point due east of and 29.50 chs. dist. from old corner of Ts. 29 and 30 S., Rs. 1 E. and 1 W., Set a basalt stone 12x12x8 ins., 8" in ground for corner of T29S R1W only, marked with 6 notches on N. and W. edges, from which

A Fir 24" dia., bears N.30°W., 2 lks. dist. mkd. T29S R1W S36 BT.

Nothing remains of the old corner but the stump of one of the bearing trees with the marks still upon it. I reestablish the corner for T30S R1W as follows: Set a basalt stone 15x12x6 ins., 10" in ground for cor. of T30S R1W, marked with 6 notches on S. and W. edges; and raised a mound of stone, 2 ft. base, 1½ ft. high, SW. of corner. Pits impracticable. No trees - - limits.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Contract #797, dated April 19, 1910 - (DCSO records Vol. 15 Page(s) 6134)

The SE. cor. of T29S R1W, which is a basalt stone 4x8x8 ins. above ground, firmly set, marked and witnessed as described by the Surveyor general.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 12, 1968 - C.S. File 54/59-85

Found Fir stump, out of place, opened for scribe marks "BS". By using 40" Pine stump line tree, 71.9 ft. South of corner, Set Brass cap at cor. mkd:

R	T 29	S	R
1	S 36	S31	1
W	S 1		E
1968			

I set this corner 211.2 ft. North of ¼ S31 only, T29-1E.
(Cont. Next Page)

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 100143

PRIMARY CORNER DESCRIPTION SE. Cor. Section 36; T29-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs- Laurel, N.55°W., scribed T29S R1W S36 CS BT.
14" Cedar N.51°E., 70.0 ft. mkd. T29S R1E S31 CS BT.
No trees available in SW. quadrant.

William Ruppert - For: U.S. Forest Service - Jan. 1978 -
M 70-2

Found - 1" Pipe with 1968 DCSO brass cap.
54" Pine stump, S.01°07'E., 72.7 ft.
21" D.Fir windfall, S.15°53'E., 59.0 ft., probably
moved.
15" Incense Cedar N.49°36'E., 70.2 ft. visible
scribe.
17" Madrone N.55°43'W., 97.3 ft. visible scribe.
New BT - 6" D.Fir S.26°59'W., 60.3 ft. "T30S R1W S1 BT"