

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only: T29-1W

| | |
|------------|------------------|
| Alias_____ | Description_____ |
| Alias_____ | Description_____ |
| Alias_____ | Description_____ |
| Alias_____ | Description_____ |

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 14 Page(s) 6061)

Set a basalt stone 15x14x4 ins., 10" in ground for ¼ sec. cor. mkd. ¼ on W. face, from which

- A Fir 12" dia., bears N.21°E., 54 lks. dist. mkd. ¼ S31 BT
- A Fir 16" dia., bears S.79°W., 44 lks. dist. mkd. ¼ S36 BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Contract #797, dated April 19, 1910 - (DCSO records Vol. 15 Page(s) 6134-35)

The ¼ sec. cor. on E. bdy. sec. 36, T29S R1W which is a basalt stone 5x14x4 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I re-establish this cor. in its original position as the ¼ sec. cor. on E. bdy. sec. 36 T29S R1W only as follows:

Stone already set and described, from which

- A Fir 16" dia., bears S.79°W., 44 lks. dist. mkd. ¼ S36 BT
 - A Fir 10" dia., bears N.40°W., 80 lks. dist. mkd. ¼ S36 BT
- I obliterate marks on former bearing tree in T29S R1E.

Douglas Co. Surveyors Office - John M. Powell, and crew - May 15, 1969 - C.S. File 54/82-58

Looked for, not found. Cor. for 30 & 31, T29-1E and this corner which lie approx. 3 chains apart, fall in edge of road and also large shale pit. Found forest location tag approx. 12 chains South of corners. Also forest location tag 10 chains East of corners. I ran line N. and W. chaining the E-w line with no results.