

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 100443

PRIMARY CORNER DESCRIPTION Cor. Secs. 13 & 24 only (East); T29-1W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 14 Page(s) 6063)

Set a basalt stone 15x12x8 ins., 10" in ground for cor. of secs. 13 and 24, marked with 3 notches on N. and S. sides, from which

A Fir 16" dia., bears S.87°W., 97 lks. dist. mkd. T29S R1W S24 BT.

A Fir 14" dia., bears N.40°W., 25 lks. dist. mkd. T29S R1W S13 BT.

Cor. used and tied in GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated Dec. 21, 1920 - (DCSO records Vol. 15 Page(s) 6140)

Douglas Co. Surveyors Office - John M. Powell, and crew - June 9, 1969 - C.S. File 54/82-75

Looked for, not found.

Second time I have looked for this corner. I have run into this cor. now from the S. and the N. Also, from the approx. line between Secs. 13 & 24. Orig. trees good large firs however, I just don't find them. Good N-S blazed line also some E-W blazes. One area possible burn.