

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated Dec. 21, 1920 - (DCSO records Vol. 15 Page(s) 6140)

-----  
Set a basalt stone 20x8x6 ins., 15" in the ground, for closing cor. of secs. 7 and 18, marked CC on E., with 2 grooves on N. and 4 grooves on S. face, from which  
A Fir 14" dia., bears N.58°E., 64 lks. dist. mkd. T29S R1E S7 CC BT.  
A Fir 10" dia., bears S.41°E., 41 lks. dist. mkd. T29S R1E S18 CC BT.  
No iron post available for this corner.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 6, 1969 - C.S. File 54/82-82

-----  
Found - 14" D.Fir now 18", N.58°E., 42.2 ft. shows good scar  
10" D.Fir now 14", S.41°E., 27.1 ft. shows good scar  
20x8x6 stone firmly set at sec. cor. mkd. 4 notches on the South, 2 on the East, CC on the East.

Set Brass cap at cor. mkd: County Surveyors Office

	T	29	S	
R			S 7	R
1	S13		S 18	1
W			1969	E

New BT - 13" D.Fir N.73°W., 17.7 ft. scribed T29S R1W S13 CC CS BT.