

PRIMARY CORNER DESCRIPTION North 1/4 Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10598)

Set a basalt stone 18x6x6", 12" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 12" dia., bears N.10°W., 15 lks., mkd: ¼ S19 BT.

A cedar, 7" dia., bears S.75°E., 9 lks., mkd: ¼ S30 BT.

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10617-8)

The old ¼ sec. cor. which is a basalt stone, 6x6x6" above ground, firmly set, marked & witnessed as described by the surveyor general. Hereafter this cor. will refer to sec. 30 only. I obliterate marks on BT N. of line, and take new BT; also obliterate marks on N and mark ¼ on S face of stone; from which

(Old BT) A cedar, 8" dia., bears S.75°E., 9 lks., mkd: ¼ S30 BT.

(New BT) A fir, 20" dia., bears S.13°W., 34 lks., mkd: ¼ S30 BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart - Aug. 4, 1981 - C.S. File 61/27-28

Found - Orig. 18x6x6" stone, now 14x6x6" buried 3" in the ground. Stone is broken into several pieces but still in its orig. position. The North face is marked with "¼" & also some other marks meant to obliterate the ¼. The south face appears to be marked with the letters E A or H A, rather than ¼ as called for in Resurvey.

BTs- 18" Fir (orig. 12") bears N.10°W., 9.9 ft. with an obliterated "1 3 BT"

8" cedar (orig. 7") down, rotted, & buried with a scribed "0" visible in a rotted open blaze, bears S.75°E., 6.5 ft. to the center of the stump hole (Rec. 5.9 ft.)

25" Fir (orig. 20") stump per resurvey, bears S.13°W., 25.8 ft. or 39 lks. (Rec. 22.4 ft. or 34 lks.) I open & find scribing: ¼ S30 BT.

Set - Brass cap marked DOUGLAS CO. SURVEYOR T29S

I bury stone next to cap ¼ 30

on the south, flush w/ ground. R1E

1981

continued next page

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION North 1/4 Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 10" Fir bears S.35°W., 91.7 ft., scribed ¼ S30 CS
BT (double blaze).
20" Fir bears N.83°W.. 53.2 ft., scribed ¼ S19 CS BT
(double blaze).
10" Fir bears N.23°E., 20.2 ft., scribed ¼ S19 CS BT
(double blaze).
40" Fir stump, 2½ ft. tall, SET Boat Spike in top,
bears S.23°W., 54.2 ft.
DCSO BT Tags on all trees
Note - Corner bears N.40°W., 51 ft. from Centerline of
Rd#298C