

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10676)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 6}{S\ 7}$
1921

from which

A madrona, 20" dia., bears N.80°E., 90 lks., mkd: 1/4 S6 BT.
A fir, 8" dia., bears S.70°E., 52 lks., mkd: 1/4 S7 BT.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - 9/3/1974 - C.S. File 57/8-1

Found - 1921 US GLO brass cap properly mkd. From which:

An orig. 8" Fir, now a 24" sugar pine bears S.70°E., 34.3 ft. We open and find good scribing "T" approx. 7" inside of tree.

We find no trace of the orig. NE bearing tree.

New BT - A 6" D.Fir, bears N.18 1/2°E., 50.0 ft. scribed "1/4 S6 CS BT".

Compass declination setting = 20° East.