

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 141100

PRIMARY CORNER DESCRIPTION N 1/4 Cor. Sec. 6 only, T30-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 26 Page(s) 10986)

Point for the ¼ sec. cor. of sec. 6 only
Set a conglomerate stone, 20x12x5", 15" in the ground, for ¼ sec. cor., of sec. 6 only, marked ¼ S6 on S face, from which
A fir, 18" dia., bears S.57°E., 50 lks., mkd: ¼ S6 BT.
A fir, 18" dia., bears S.73°W., 26 lks., mkd: ¼ S6 BT.
No iron post available for this corner.

Douglas Co. Surveyors Office - R.B. Kimberling - 5/31/1977
(added 6/21/2016) - C.S. file 59/34-26

Reported as not found
Found - A mound of sedimentary stone four ins. high, one ft. dia., with possible trace "1" chiseled marking on one stone 5"x3"x2". From stone mound BT is behind high stump 24" dia., and was probably disturbed by logging operation - an aged pile of logs is 20 ft. SE.
From a point 2.0 ft. SE of stone mound:
A 14" dia., fir stump and log bears N.67°W., 33.0 ft. found scribing "3 " other scribing has been axed out and tree died without any healing. A possible stump hole bears S.73°W., 17.2 ft. (rec. 18" dia., fir, S.57°E., 33.0 ft., 18" dia., fir S.73°W., 17.2')

No monument set, no new accessories.
Note - If corner set from S¼ Sec. 31 it would be 0.5 ft. north of mound of stone.
Dec. 20°E.