

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page 10594)

-----  
Set a basalt stone 15x14x8", 10" in the ground for cor. of secs. 29, 30, 31, & 32 mkd with 1 notch on S & 5 notches on E edges, from which  
A fir, 7" dia., bears N.83°E., 23 lks mkd: T29S R1E S29 BT  
A fir, 10" dia. bears S.44°E., 32 lks mkd: T29S R1E S32 BT  
A fir, 8" dia., bears S.12°W., 20 lks mkd: T29S R1E S31 BT  
A fir, 10" dia. bears N.36°W., 51 lks mkd: T29S R1E S30 BT

Douglas Co. Surveyors Office - Clell Goodwin - Lenora Lading - Gary Heichel - Mel Dunlop - 1/7/1976 - C.S. File 59/2-2

-----  
Found - A 13x12x8" Basalt stone with 5 notches on the east and 1 notch on the south.  
Orig. 7" now 10" fir bears N.83°E., 15.5 ft.  
Orig. 10" now 18" fir bears S.44°E., 20.9 ft.  
Orig. 8" now 10" fir bears S.12°W., 13.2 ft.  
Orig. 10" now 20" fir bears N.36°W., 33.7 ft.  
All alive and well healed  
Set - A 1"x30" IP with brass cap stamped T29S R1E  
DOUGLAS CO. SURVEYOR S 30|S 29  
1976 S 31|S 32

At the corner point we set the original stone north of the corner.  
Compass Declination 20° East.  
NOTE - Corner is located approx. 400' above Rd. #2980 and 70' into the timber from the north end of the clear cut.