

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 29 & 30 only, North

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10596-7)

Set a conglomerate stone 18x12x6", 12" in the ground for cor. of secs. 19, 20, 29, & 30 mkd with 2 notches on S & 5 notches on E edge, from which

- A fir, 6" dia. bears N.16°E., 13 lks. mkd: T29S R1E S20 BT
- A fir, 6" dia., bears S.75°E., 6 lks. mkd: T29S R1E S29 BT
- A fir, 6" dia. bears S.33°W., 11 lks. mkd: T29S R1E S30 BT
- A hemlock, 5" dia., bears N.22°W., 14 lks., mkd: T29S R1E S19 BT.

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10617)

The old cor. of secs. 19, 20, 29, & 30, a basalt stone, 6x12x6" above ground, firmly set, marked & witnessed as described by the surveyor general. Hereafter this cor. will refer to secs. 29 & 30 only. I obliterate marks on BTs referring to secs. 19 & 20.

From the corner, (Old BTs)

- A fir, 6" dia., bears S.75°E., 6 lks. mkd: T29S R1E S29 BT
- A fir, 6" dia. bears S.33°W., 11 lks. mkd: T29S R1E S30 BT