

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10666)

-----  
Point for cor. of secs. 17, 18, 19, & 20, falls on sloping bedrock; impracticable to set iron post, and no stones available for mound; therefore, at exact corner point, Cut a cross (x) with 5 grooves E and 3 grooves S of cross, for cor. of secs. 17, 18, 19, & 20; from which

- A fir, 12" dia. bears N.67°E., 35 lks mkd: T29S R1E S17 BT
- A fir, 10" dia. bears S.55°E., 40 lks mkd: T29S R1E S20 BT
- A fir, 8" dia. bears S.21°W., 75 lks. mkd: T29S R1E S19 BT
- A W.Oak, 5" dia., bears N.33°W., 60 lks., mkd: T29S R1E S18 BT.

U.S. Forest Service, Tiller Ranger District (Filed Nov. 16, 1973) - C.S. File 56/40-43

-----  
Never found.