TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10669)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor., with brass cap marked

¼
S 18|S 17
1921

from which
A fir, 40" dia., bears S.41°E., 26 lks., mkd: ¼ S17 BT.
A fir, 20" dia., bears S.63°W., 20 lks., mkd: ¼ S18 BT.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Terrie Plouff & Teresa Buley - 10/8/1981 - C.S. File 61/29-13

Found - 1921 Brass Cap stamped: ¼ S18 S17 1921, on a 1"x36" I.P., buried with 30" above ground.
We did NOT locate any evidence of the two orig. bearing trees. As we are unsure of monument position as location of orig. ¼ corner position, we check the following collateral call evidence: 1) South 184.8 ft. right bank of river (Rec,.) this bearing & distance falls on right shore of South Umpqua River. 2) South 99 ft trail course E and W (Rec,.) this bearing and dist. falls short of presently traveled roadway ditch approx 5 ft. 3) North 33 ft. creek bed course SE (Rec,.) this bearing & dist. falls in current creek bed, considerable erosion in this area makes it impossible to determine 1921 creek bed location.

Set - To perpetuate position of found monument as evidence of ¼ corner location, we bury a 1"x30" I.P. w/attached BC, 24" into ground. Cap is stamped: Douglas County Surveyor T29S R1E ¼ S18 S17 1981. (with a mound of stones around.)

New BTs- 18" Fir, double blazed & scribed ¼ S18 CS BT bears N.26½°W., 16.6 ft.
8" Fir, double blazed & scribed ¼ S18 CS BT bears S.64½°W., 36.0 ft.
9" Fir, double blazed & scribed ¼ S17 CS BT bears S.12°E., 27.8 ft.
10" Ash, double blazed & scribed ¼ S17 CS BT bears N.29°E., 22.5 ft.