

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10670)

-----  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 7, 8, 17, & 18, with brass cap mkd

T29S R1E  
S 7 | S 8  
S 18 | S 17  
1921

from which

- A fir, 12" dia., bears N.42°E., 19 lks mkd: T29S R1E S8 BT
- A fir, 40" dia. bears S.23°E., 62 lks mkd: T29S R1E S17 BT
- A fir, 24" dia. bears S.83°W., 47 lks mkd: T29S R1E S18 BT
- A dogwood, 6" dia., bears N.55°W., 37 lks., mkd: T29S R1E S7 BT.

U.S. Forest Service, Tiller Ranger District - 2/15/1945 (Filed Nov. 16, 1973) - C.S. File 56/40-48

- 
- Found - Brass cap  
12" D.Fir N.42°E., 19 lks.  
6" D.W. N.55°W., 37 lks., down.  
40" D.Fir, S.23°E., 62 lks.  
24" D.Fir, S.83°W., 47 lks.

Note - To reach cor. use FS Rd. 2815