

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION North ¼ Cor. Sec. 29 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10597)

Set a conglomerate stone 15x12x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

- A fir, 8" dia., bears N.73°W., 9 lks., mkd: ¼ S20 BT.
- A fir, 8" dia., bears S.75°E., 7 lks., mkd: ¼ S29 BT.

GL0 survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10616)

The old ¼ sec. corner, which is a conglomerate stone, 5x12x6" above ground, firmly set, marked & witnessed as described by the Surveyor General. Hereafter, this corner will refer to Sec. 29 only. I obliterate marks on BTs N of line, and take new BT; also obliterate marks on N & mark ¼ on S face of stone; from which

- (Old BT) A fir, 10" dia., bears S.75°E., 7 lks., mkd: ¼ S29 BT.
- (New BT) A fir, 12" dia., bears S.80°W., 27 lks., mkd: ¼ S29 BT.

U.S. Forest Service, Tiller Ranger District (Filed Nov. 16, 1973) - C.S. File 56/40-6 - added 4/6/2021

Never found.