

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10667)

In draw, course N
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for
¼ sec. cor., with brass cap marked

¼ $\frac{S\ 17}{S\ 20}$
1921

from which

- A fir, 20" dia., bears N.17°E., 30 lks., mkd: ¼ S17 BT.
- A fir, 20" dia., bears S.50°W., 12 lks., mkd: ¼ S20 BT.

U.S. Forest Service, Tiller Ranger District - 6/8/1948 (Filed
Nov. 16, 1973) - C.S. File 56/40-72

Found - Brass cap
20" D.F. N.17°E., 20 lks. grown over, tagged.
19" D.F. S.50°W., 12 lks. grown over.

Note - Best Route to cor. use F.S. Rd. No. 2937. Cou.d lie
in CC.