

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 241100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 5, North; T30-01E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 25 Page 10682 & Vol. 26 Page 10985)

Point for ¼ sec. cor. of sec. 5 only
Set a conglomerate stone 20x10x6", 15" in the ground for ¼ sec. cor. of sec. 5 only, mkd. ¼ S5 on S face, from which
A fir, 12" dia., bears S.38°E., 59 lks., mkd: ¼ S5 BT.
A fir, 30" dia., bears S.12°W., 27 ft., mkd: ¼ S5 BT.
No iron post available for this cor.

Douglas Co. Surveyors Office - A. Victor Cangie - Oct. 11, 1976 - C.S. File 59/24-28

Found - A 20x10x6" stone, loose and mkd. "¼ S5" on south face From which:
A 10" (recorded 12" when scribed) D. Fir bears S.44°E., (rec. S.38°E., 38.9 ft. I open and find "¼ S5 BT" as per record.
A 30" D.Fir bears S.12°W., 17.8 ft. Shows good scar & is healthy.
Set - A 1"x30" I.P. with brass cap stamped:
Douglas Co. Surveyor
T29S R1E
¼ S 5
T30S R1E
I replace found stone on south side of cap with marks facing south.
Note - Corner lies approx. 200' south of F.S. Rd. #298.