

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10590)

-----

Set a conglomerate stone 18x10x4", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A fir, 20" dia., bears N.83°E., 43 lks., mkd: ¼ S33 BT.  
An oak, 6" dia., bears S.84°W., 16 lks., mkd: ¼ S32 BT.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - 9/5/1974 - C.S. File 57/8-3

-----

Found - A conglomerate stone, loosely set, measuring 9"x10"x4" (rec. 18"x10"x4") set 7" in the ground and marked with a + chiseled on the west face  
From which:

An orig. 20" now 24" D.Fir bears N.83°E., 28.4 ft. alive and well healed, we do not open.

We find Oak wood fragments in the ground at the proper position for the orig. SW bearing tree.  
There is no remaining trace of this tree.

At the corner point we set a brass cap marked:

COUNTY SURVEYORS T 29 S  
OFFICE S 32 | S 33  
1974 ¼  
R1E

We deposit the orig. cornerstone alongside the brass cap and mark the following bearing tree:

An 18" D Fir bears N.42°W., 57.5 ft scribed "¼ S 32 CS BT"  
Compass declination set at 20° East.