

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10592)

Set a conglomerate stone 18x15x8", 12" in the ground for cor. of secs. 20, 21, 28, & 29 mkd with 2 notches on S & 4 notches on E edges, from which

- A fir, 24" dia. bears N.18°E., 20 lks mkd: T29S R1E S21 BT
- A fir, 18" dia. bears S.27°E., 39 lks mkd: T29S R1E S28 BT
- A fir, 10" dia. bears S.81°W., 37 lks mkd: T29S R1E S29 BT
- A fir, 10" dia., bears N.14°W., 6 lks mkd: T29S R1E S20 BT

FD. & used on GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10614)

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Terrie Plouff & Teresa Buley - 10/8/1981 - C.S. File 61/29-6

Found - A conglomerate stone 18"x15"x7" (Rec. 18"x15"x 8"), 14" in the ground (Rec., 12"), with two notches on the South side, 4 notches on the East side, & a chiseled X in the center of top of stone.

- BTs - 24", now 32" Fir, bears N.18°E., 13.2 ft. w/well healed blaze. 18", now 30" Fir, bears S.27°E., 25.4 ft. (Rec. 25.7 ft) with well healed blaze.
10", now 13" Fir, bears S.79½°W., 24.2 ft. (Rec. S.81°W., 24.4 ft.), with well healed blaze. This tree is leaning badly and beginning to decay.
10" Fir bears N.14°W., 4.4 ft. (Rec. 4.0 ft.) with partially healed blaze w/fragmentary scribing visible.

Set - Brass Cap on a 1"x30" IP stamped: Douglas County Surveyor T29S R1E S20 S21 S29 S28 1981

New BTs- 12" Fir bears S.63½°W., 52.3 ft., scribed T29S R1E S29 CS BT, in a double blaze.

Note - Followed blazed line from road approaching from the South to reach.