

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10657)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor., with brass cap marked

¼
S 20 | S 21
1921

from which

A fir, 10" dia., bears S.48°W., 29 lks., mkd: ¼ S20 BT.

A cedar, 12" dia., bears N.57°E., 42 lks., mkd: ¼ S21 BT.

U.S. Forest Service, Tiller Ranger District - 6/7/1948 -
(Filed Nov. 16, 1973) - C.S. File 56/40-75

Found - Brass cap

13" I.C. N.57°E., 43 lks. grown over, tagged.

10" D.Fir S.48°W., 29 lks. grown over.

Note - Best route to cor. use F.S. Rd. No. 2937 or 2941.

Sec. line marker on the old North South Trail, 1
ch. south of corner.