

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10657)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 16, 17, 20, & 21, with brass cap mkd

T29S R1E
S 17 | S 16
S 20 | S 21
1921

from which

A cedar, 24" dia., bears N.5°E., 34 lks., mkd: T29S R1E S16 BT.

A fir, 36" dia. bears S.77°E., 29 lks mkd: T29S R1E S21 BT

A fir, 18" dia. bears S.51°W., 44 lks mkd: T29S R1E S20 BT

A fir, 36" dia. bears N.14°W., 20 lks mkd: T29S R1E S17 BT

U.S. Forest Service, Tiller Ranger District - 4/30/1947 -
(Filed Nov. 16, 1973) - C.S. File 56/40-71

Found - Brass cap

26" I.C., N.5°E., 34 lks.

38" D.P., N.14°W., 20 lks. tagged

38" D.F. S.77°E., 29 lks.

20" W.F. S.51°W. 44 lks.

Note - Best route use F.S. Rd. No. 2937. Could lie in C.C.