

PRIMARY CORNER DESCRIPTION Cor. Sec. 8, 9, 16, & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10660)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T29S R1E
S 8 | S 9
S 17 | S 16
1921

from which

A hemlock, 10" dia., bears N.11°E., 13 lks., mkd: T29S R1E S9 BT.

A fir, 8" dia., bears S.24°E., 31 lks mkd: T29S R1E S16 BT

A fir, 6" dia., bears S.56°W., 29 lks mkd: T29S R1E S17 BT

A hemlock, 12" dia., bears N.11°W., 14 lks., mkd: T29S R1E S8 BT.

Cor. No. 12 HES No. 144, which is a porphyry stone, 10x22x12" above ground, firmly set, marked and witnessed as described in field notes of HES No. 144, bears N.84°17'W., 12.44 chs.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart - Janet Lundeen - May/June 1981 - C.S. File 61/24-30

Found - Orig. 1921 GLO Brass Cap, properly stamped, firmly set, protruding 5" out of ground.

Orig. 10", now 16" Hemlock with healed blaze bears N.11°E., 8.6 ft.

Orig. 8", now 9" Fir down & covered by large Fir log, bears S 24°E., unable to determine exact point for distance. Blaze appears to be on the down side of tree.

Orig. 6", now 6" Fir down & partially rotted bears S.56°W., 19.1 ft. Opened blaze & find scribed "S 17 BT".

Orig. 12", now 19" Hemlock with well healed blaze bears N.11°W., 9.2 ft.

New BTs- 11" Hemlock bears S.22°W., 26.0 ft., scribed "T 29 S R 1 E S 17 CS BT" in double blaze.

11" Fir bears S.67°E., 17.9 ft. scribed "T 29 R 1 E S 16 CS BT" in double blaze.

All BTs have DCSO BT tags.

Corner lies in timber approx. 40' East of N-S cutline.