

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10662-3)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap mkd

T29S | R1E
S 5 | S 4
S 8 | S 9
1921

from which

- A fir, 12" dia. bears N.88°E., 19 lks. mkd: T29S R1E S4 BT
- A cedar, 6" dia. bears S.50°E., 5 lks. mkd: T29S R1E S9 BT
- A fir, 10" dia. bears S.11°W., 47 lks. mkd: T29S R1E S8 BT
- A fir, 6" dia., bears N.49°W., 5 lks., mkd: T29S R1E S5 BT

Douglas Co. Surveyors Office - Clell Goodwin - Lenora Lading - Gary Heichel - Mel Dunlop - 1/7/1976 - C.S. File 59/2-6

Found - A Brass cap on a 2" IP projecting 6" out of the ground and marked

U.S. GOVERNMENT LAND OFFICE SURVEY
T29S R1E
S 5 | S 4
S 8 | S 9
1921

From which:

- An orig. 12" now 18" fir bears S.88°E., 12.1 (call: N.88°E., 12.5 ft) well healed
- An orig. 6" still 6" cedar bears S.53°E., 2.5 ft (call S.50°E., 3.3 ft) visible scribe on rotted face
- An orig. 10" now 11" fir bears S.14°W., 31.0 ft. (call S.11°W., 31.0 ft) well healed.
- An orig. 6" still 6" fir bears N.49°W., 4.0 ft. (call N.49°W., 3.3 ft) well healed

Compass declination 20° East