

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 33 only, South

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page 10571 & Vol. 26 Page 10969)

Set a conglomerate stone 15x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 6" dia., bears N.23°E., 18 lks., mkd: ¼ S33 BT.
A fir, 6" dia., bears S.45°W., 16 ft., mkd: ¼ S4 BT.

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 25 Page 10681 & Vol. 26 Page 10984)

The ¼ sec. cor. est. for secs. 4 & 33, which is a conglomerate stone 8x6x5" above ground, firmly set, marked & witnesses as described by the surveyor general. Hereafter this cor. will refer to sec. 33 only. I mark the cor. stone ¼ S33 on N face; from which
A fir, 6" dia., bears N.23°E., 18 lks., mkd: ¼ S33 BT, old BT.
A pine, 44" dia., bears N.57°W., 48 lks., mkd: ¼ S33 BT, new BT.
I obliterate the marks on the old BT in sec. 4.

Douglas Co. Surveyors Office - A. Victor Cangie - M. Tompkins - K. Cheney - Oct. 6, 1976 - C.S. File 59/24-25

Found - A 13x10"x6" (rec. 15"x8"x6") stone disturbed. I find no identifiable marks on stone.
An orig. 44" now 48" Pine stump. I open & find faint "T" and part of a "B", bears N.57°W., 31.7 ft.
Found no other trees.
Set - From above Pine stump I set: A 1"x30" I.P. with brass cap stamped: Douglas Co Surveyor T29S R1E
1976 ¼ S 33
T30S R1E
New BTs- A 9" D.Fir bears S.13°W., 28.1 ft. mkd. "¼ RP CS BT" in a double blaze.
An 11" D.Fir bears N.74°W., 27.4 ft. mkd. "¼ S33 CS BT" in a double blaze.