

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10593)

Set a conglomerate stone 20x15x12", 15" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 12" dia., bears N.31°W., 28 lks., mkd: ¼ S21 BT.
A fir, 15" dia., bears S.44°W., 72 lks., mkd: ¼ S28 BT.

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10614)

The ¼ sec. cor., which is a conglomerate stone, 5x12x12" above ground, firmly set, marked & witnessed as described by the surveyor general, except that the N BT is dead & fallen. I take new BT, from the corner
(New BT) A cedar, 15" dia., bears N.64°W., 65 lks., mkd: ¼ S21 BT.
(Old BT) A fir, 15" dia., bears S.44°W., 72 lks., mkd: ¼ S28 BT.

Douglas Co. Surveyors Office - Clell Goodwin - Gary Langlitz - Lenora Ladig - Vic Cangie - 12/22/1975 - C.S. File 57/39-44

Found - A conglomerate stone marked with an "X".
From Which:
An orig. 15" now 27" W.Fir bears S.44°W., 47.5 ft. with visible scar.
A 15" now 24" I. cedar scribed in the retracement survey bears N.64°W., 42.9 ft. with faint scar.
Set - A 1"x30" IP with brass cap stamped T29S R1E
DOUGLAS CO. SURVEYOR ¼ S 21
1975 S 28
with the stone alongside.
Compass declination 20° East