

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10658)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 16}{S\ 21}$
1921

from which

A fir, 28" dia., bears N.11°W., 60 lks., mkd: 1/4 S16 BT.

A fir, 40" dia., bears S.20°W., 43 lks., mkd: 1/4 S21 BT.

U.S. Forest Service, Tiller Ranger District - 4/30/1948 -
(Filed Nov. 16, 1973) - C.S. File 56/40-70

Found - Brass cap
28" D.F. N.11°W., 60 lks.
46" D.F. S.20°W., 43 lks.

Note - Best route to cor. use F.S. Rd. No. 2921 or 2937.
The old North South Trail crosses the Sec. line
about 1 1/2 chs west of corner.