

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page(s) 10663-4)

-----

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for  
¼ sec. cor., with brass cap marked

S 4  
¼ S 9  
1921

from which

A cedar, 16" dia., bears N.73°E., 32 lks., mkd: ¼ S4 BT.

A fir, 18" dia., bears S.71°E., 17 lks., mkd: ¼ S9 BT.

Douglas Co. Surveyors Office - Gary Langlitz - Jerry Jacson -  
A. Vic Cangie - Peter L. Earle - 1/7/1976 - C.S. File 59/2-5

-----

Found - Iron pipe, firmly set properly marked with brass cap  
by GLO.

An orig. 16" Incense cedar, now a 19" snag, well-  
healed, bears N.73°E., 21.1 ft

An orig. 18" D.Fir, now a 20" snag well-healed,  
bears S.67°E., 11.7 ft. ( rec. S.71°E., 11.7 ft.)

New BTs- A 10" G.Fir bears S.41°E., 14.8 ft., scribed "¼ S9  
CS BT" on a double blaze

7" D.Fir bears N.38°E., 16.8 ft., scribed "¼ S4 CS  
BT" on a double blaze

Compass Declination Setting: 20° East