

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4; & 33 T28-01E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 24 Page 10257 & Vol. 25 Pages 10627-8)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 33}{S\ 4}$
1921

from which

- A fir, 16" dia., bears N.17°W., 74 lks., mkd: 1/4 S33 BT.
- A fir, 16" dia., bears S.46°E., 20 lks., mkd: 1/4 S4 BT.

Douglas Co. Surveyors Office - A. Victor Cangie - Mike Tompkins - 11/8/1976 - C.S. File 59/26-10 (added 4/11/2016)

Not found?

Found - An East-West blazed line. Corner is supposed to be .6 chains out of a creek and the calls say he ascends 20' out of said creek to bench. We find an old clearcut unit in this area with no trees standing and raked with skid roads and trails. We retrace blazes and set compass east and search area where corner should be according to creek calls. We find no traces of monument or BTS.

Compass dec. 20°E