

PRIMARY CORNER DESCRIPTION South Cor. Secs. 33 & 34 only;

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Pages 10571-2 & Vol. 26 Pages 10969-70)

Point for cor. of secs. 3, 4, 33 & 34 falls on exposed bedrock, on which I cut a cross, (x) at exact cor. point, with 3 notches E & W of cross, from which

A fir, 15" dia. bears N.23°E., 40 lks mkd: T29S R1E S34 BT
A fir, 24" dia., bears S.18°E., 39 lks mkd: T30S R1E S3 BT
A fir, 16" dia., bears S.30°W., 54 lks mkd: T30S R1E S4 BT
A fir, 7" dia., bears N.12°W., 20 lks mkd: T29S R1E S33 BT

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 25 Page 10681 & Vol. 26 Page(s) 10984)

The cor. set for secs 3, 4, 33, & 34, is a cross (X) on bedrock, witnessed as described by the surveyor general. Hereafter this cor. will refer to secs. 33 & 34 only. I mark the rock S34 on NE & S 33 on NW side of the cross and obliterate the marks on the BTs for secs. 3 & 4.

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14077)

The cor. of secs. 33 & 34 only, which is a cross (X) on bedrock, with 3 grooves on E & W side of cross. At point for corner,
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 33 & 34 only, with brass cap mkd

T29S	R1E
<u>S 33</u>	<u>S 34</u>
T30S	R1E
S 4	
1937	

from which

A fir, 20" dia., bears N.23°E., 40 lks., blaze healed; I do not open (Old BT)
A fir, 10" dia., bears N.15¼°W., 20 lks., blaze healed; I do not open (Old BT)

Douglas Co. Surveyors Office - Larry E. Monrean - P. Earle - Nov. 3, 1976 - C.S. File 59/26-8

Found - 1937 GLO Brass properly stamped, firmly set in mound of stone. continued next page

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION South Cor. Secs. 33 & 34 only;

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 15" Fir, now a snag, bears N.20½°E., 28.8 ft.
(Rec. N.23°E.,, 26.4 ft.) Tree has well healed
blaze.

A 7" Fir, now 12", bears N.14°W., 15.8 ft. (Rec.
N.12°W., 13.2 ft.) Tree has well healed blaze.

New BT - A 13" I.Cedar, bears N.34½°E., 32.1 ft. Tree double
blazed & scribed "T29S R1E., S34 CS BT"