

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10586)

Set a basalt stone 18x15x12", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A pine, 14" dia., bears N.47°E., 59 lks., mkd: ¼ S34 BT.
A fir, 6" dia., bears S.85°W., 32 lks., mkd: ¼ S33 BT.

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Chuck LeBold & Joe Sheriff - Feb. 3, 1977 - C.S. File 59/29-26

Found - 12" x 8" x 10" Rock in vicinity, no visible marks on rock. Stone out of ground, S.30°E., 1.0 ft. from true corner. Location as determined from accessories.

Orig. 6" now 17" D.Fir with healed blazes bears S.83°30'W (Rec. S.85°W.) 21.12 ft. (Rec. 32 lks.). Do not open.

Orig. 14" now 18" Ponderosa Pine visible scribes "¼ S34" bears N.48°30'E., 38.94 ft. (Rec. N.47°E., 59 lks.). Forest Service Form 448 attached.

Placed County BT tags on both trees. BTs are alive.

Set - 2½" Brass cap 14" above ground with a surrounding 2'x2' rock mound mkd: Douglas County Surveyors T 29 S

Office ¼ S 33 | S 34
1977 R1E

Found stone buried adjacent to pipe. No new BTs scribed.

Note: Corner lies on a gentle south slope 100 ft. north of clearcut & 350 ft. east of F.S. Rd. No. 29814.

Compass declination: 18½°E.