

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10586-7)

-----  
A fir, 6" dia., for corner to secs. 27, 28, 33, & 34, I mark T29S S27 on NE, R1E S34 on SE, S33 on SW, and S28 on NW side, with 1 notch on S & 3 notches on E side, from which  
A fir, 8" dia., bears N.23°E., 48 lks mkd: T29S R1E S27 BT  
A fir, 20" dia. bears S.70°E., 17 lks mkd: T29S R1E S34 BT  
A fir, 16" dia. bears S.67°W., 13 lks mkd: T29S R1E S33 BT  
A fir, 36" dia. bears N.67°W., 45 lks mkd: T29S R1E S28 BT

Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Chuck LeBold & Joe Sheriff - Feb. 3, 1977 - C.S. File 59/29-25

-----  
Found - Orig. corner tree (1910 6" Fir) is missing.  
Orig. 8" D.Fir, now 17" rotted stump, bears N.23°E., 31.68 ft. with visible scribe R1 S2.

Set - 2½" brass cap set 6" above ground with surrounding 1½'x1½' rock mound, stamped:  
Douglas County Surveyor T29S  
Office S 28 | S 27  
1977 S 33 | S 34  
R1E

New BTs- 16" G.Fir bears N.2¾°W., 39.5 ft. scribed T29S R1E S28 CS BT.  
9" Yew bears N.71¾°E., 44.7 ft. scribed T29S R1E S27 CS BT.  
19" D.Fir bears S.69½°E., 76.0 ft. scribed T29S R1E S34 CS BT  
13" Hemlock bears S.26¼°W., 148.1 ft. scribed T29S R1E S33 CS BT.

Attached County BT tags to all trees.  
Note - Corner lies in creek bottom. 40 ft. East of F.S. Rd. No. 2921C.  
Compass declination 20°E.