

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO records Vol. 25 Page(s) 10588)

Set a conglomerate stone 18x14x5", 12" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
A fir, 6" dia., bears N.74°E., 10 lks., mkd: ¼ S27 BT.
A fir, 36" dia., bears N.68°W., 35 lks., mkd: ¼ S28 BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Terrie Plouff & Teresa Buley - 10/7/1981 - C.S. File 61/27-5

Found - Orig. 18"x14"x5" stone, now 15"x12"x5" with ¼ on the West face and + on top.
Orig. 6", now 8" Fir stump, approx. 7 ft. tall, bears N.74°E., 6.6 ft., with well healed scar.
Orig. 36", now 39" Fir, down but still sound; I open small area & find scribed ¼. Tree bears N.68°W., 23.1 ft. to stump hole.
Set - I reference location of orig. stone & set Brass Cap in its place marked: Douglas Co. Surveyor T29S ¼ S28 S27 R1E 1981. (I bury stone along West side of cap).
New BTs- I scribe Cs BT on orig. 6", now 8" Fir stump, above orig. scar.
Set Boat spike stamped BO 1 in 48" Fir stump, bears S.61½°E., 47.7 ft
Set B. spike stamped BO 2 in 48" Fir stump, bears N.11°W., 56.0 ft.
Set PK Nail in top of boulder 7 ft x 11 ft., 3 ft. high bears S.17½°E., 103.6 ft.