TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCS0 records Vol. 25 Page 10650)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor., with brass cap marked

¼
S 16 | S 15
1921

from which
A fir, 14" dia., bears N.18°E., 39 lks., mkd: ¼ S15 BT.
A fir, 20" dia., bears N.35°W., 87 lks., mkd: ¼ S16 BT.

U.S. Forest Service, Tiller Ranger District (Filed Nov. 16, 1973) - C.S. File 56/40-2

Never found.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Terrie Plouff & Teresa Buley - 10/1/1981 - C.S. File 61/29-2

Found - Orig. Brass Cap (1921), firmly set, protruding 5" out of ground, marked T29S R1E ¼ S16 S15 1921
BTs - Orig. 14", now 21" Fir w/good scar bears N.16°E., 53.6 ft.(rec. N.18°E., 25.7 ft.)
Orig. 20", now 25" Fir w/good scar bears N.38°W., 25.6 ft.(N.35°W., 57.4 ft.)
There appears to be some mix-up on original notes.
New BTs- 9" Cedar bears N.22°W., 65.7 ft., scribed ¼ S16 CS BT (dbl. blaze)
11" Madrone bears S.43°E., 29.6 ft., scribed ¼ S15 CS BT in double blaze.