

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10651)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 9, 10, 15, & 16, with brass cap mkd

T29S	R1E
S 9	S 10
S 16	S 15
1921	

from which

- A fir, 10" dia., bears N.47°E., 28 lks., mkd: T29S R1E S10
BT.
- A fir, 16" dia., bears S.78°E., 13 lks., mkd: T29S R1E S15
BT.
- A fir, 5" dia., bears S.39°W., 18 lks., mkd: T29S R1E S16
BT.
- A fir, 24" dia., bears N.28°W., 25 lks., mkd: T29S R1E S9
BT.

U.S. Forest Service, Tiller Ranger District - 4/7/1961 -
(Filed Nov. 16, 1973) - C.S. File 56/40-52

Found - brass cap

No information on BTs

Note - Best route to corner, use FS Rd. No. 284