

TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10654)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 3, 4, 9, & 10, with brass cap mkd

T29S	R1E
S 4	S 3
S 9	S 10

1921

from which

- A fir, 18" dia., bears N.42°E., 25 lks., mkd: T29S R1E S3 BT.
- A fir, 12" dia., bears S.81°E., 45 lks., mkd: T29S R1E S10 BT.
- A fir, 24" dia., bears S.21°W., 20 lks., mkd: T29S R1E S9 BT.
- A fir, 14" dia., bears N.69°W., 30 lks., mkd: T29S R1E S4 BT.

Douglas Co. Surveyors Office - Gary Langlitz - Peter Earle - 8/13/1974 - C.S. File 57/2-13

Found - 1921 US GLO brass cap properly marked. From which:
A Fir, orig. 18" now 19", bears N.42°E., 22.8 ft. (rec. N.42°E., 16.5 ft.) alive and well healed.
A Fir, orig. 12" now 15", bears S.81°E., 29.7 ft. alive and well healed.
A Fir, orig. 24" now 24", bears S.21°W., 13.2 ft. alive and well healed.
A Fir, orig. 14" now 16", bears N.69°W., 19.8 ft. alive and well healed.

We do not remonument.