TOWNSHIP 29 RANGE 01E POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer, Group No. 62, dated Dec. 21, 1920 - (DCSO records Vol. 25 Page 10656)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor., with brass cap marked

¼
S 4|S 3
1921

from which
A fir, 10" dia., bears N.20°E., 32 lks., mkd: ¼ S3 BT.
A fir, 10" dia., bears N.21°W., 45 lks., mkd: ¼ S4 BT.

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Teresa Buley - Oct. 27, 1981 - C.S. File 61/29-18

Found - Orig. 1921 B.C. leaning to the Southwest, in a mound of stone. The cap was lying lose1y in the mound of stone and marked: 1/4 S4|S3 1921 , from which bearing trees bear:
Orig. l0", now 11" Fir, alive, with good scar, bears N.20°E., 20.4 ft (Rec. 21.1 ft.).
Orig. 10" now 12" Fir, alive, with good scar, bears N.20°W., 28.7 ft. (Rec. N.21°W., 29.7 ft.).

Set - Since the B.C. found was not firmly set in the ground as per the Orig. notes, I place cap at Rec. bearing & distance from both Orig. trees and build large mound of stones around cap. (Ground is bedrock, unable to dig hole).
Orig. 10" now 11" Fir bears N.20°E., 21.1 ft.
Orig. 10" now 12" Fir bears N.21°W., 29.7 ft.
17" Fir scribed ¼ S3 CS BT in dble. blaze bears S39°E., 44.7 ft.
20" Cedar scribed ¼ S4 CSBT in dble. blaze bears S15°W., 41.3 ft.