

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 34 only

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

GLO survey by Fred Mensch, US Deputy Surveyor, under contract No. 797, dated April 19, 1910 - (DCSO recs Vol 25 Page 10572) & Vol. 26 Page 10970)

Set a conglomerate stone 15x8x4", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 36" dia., bears N.46°W., 19 lks., mkd: ¼ S34 BT.
A madrone, 12" dia., bears S.44°W., 21 lks., mkd: ¼ S3 BT.

GLO survey by Fred Mensch, Cadastral Engineer, under special instructions Dated June 7, 1922 - (DCSO records Vol. 25 Page 10680 & Vol. 26 Page 10984)

The ¼ sec. cor. on S bdy of sec. 34, which is a conglomerate stone, 5x8x4" above ground, firmly set, marked & witnessed as described by the surveyor general, bears E.

GLO resurvey by Norman D. Price, Cadastral Engineer, Leonard Carter, Public Land Surveyor, and George F. Dawson Jr., Transitman, under Group No. 175 surveyed April/Aug. 1937 - (DCSO records Vol. 34 Page(s) 14076)

The orig. ¼ sec. cor. of secs. 3 & 34, which is a conglomerate stone, 10x6x4", firmly set, mkd. ¼ on N face. Hereafter this cor. will refer to sec. 34 only.
At point for corner,
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with the orig. stone deposited at the base, for ¼ sec. cor. of sec. 34 only, with brass cap mkd ¼ S 34
1937 from which
A fir, 45" dia., bears N.48°W., 20 lks., blazed healed; I do not open (Old BT)
A madrona, 13" dia., bears S.44°W., 22 lks., mkd. ¼ S 3 BT. I obliterate the marks on this tree. (Old BT)
A pine, 28" dia., bears N.28¼°E., 99 lks. mkd. ¼ S34 BT.

Dennis Gaylord, USFS & DCSO Deputy - Walt Barton - Feb. 24, 1977 - C.S. File 59/29-36

Found - 1937 GLO brass cap 8" above ground properly stamped. (Township & range not shown on brass cap).
A 50" D.Fir bears N.48°W., 13.2 ft. w/healed scar.
A 31" P.Pine bears N.28½°E., 65.34 ft. w/healed scar
A 15" Madrone bears S.44°W., 14.52 ft. Previously opened face, all scribing destroyed.
Placed County BT signs on Fir & Pine.
Corner is 800 feet east of F.S. Rd. #2930A